



# 4MP IP Turret Camera with People & Vehicle Detection

## O4VT2

2.8mm fixed lens, white housing

### Features

- Supports up to 4MP @ 30fps
- H.265/H.264 compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: 100' (depending on scene reflection)
- True WDR
- MicroSD card slot up to 256GB max (card not included)
- Built-in Microphone
- Conformant with ONVIF Profile G/S/T
- Line crossing, object detection, region intrusion and video blurring detection
- IP67 weather resistance
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guideline



Junction Box Included



### Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS, 4MP
Maximum Resolution	2560 x 1440 (4MP)
Field of View	94° (H), 50° (V), 115°(D)
Minimum Illumination	0.005 lux @ F1.6, AGC ON; 0 lux with IR
Image Settings	Region of interest, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Defog, Sharpen, Noise Reduction
Day/Night	Smart IR up to 100' (depending on scene reflection)
Compensation	True WDR, BLC, HLC
Electronic Shutter Speed	1/2 - 1/100000 sec.
DNR	3D DNR
Angle Adjustment	Pan 0°-360°, Tilt 0°-75°, Rotation 0°-360°

### Video Specifications

Main Resolution	2560x1440 / 2304x1296 / 1920x1080 @ 30fps
Sub stream Resolution	720p (1-15fps), D1, CIF (1-30fps)
Third Stream	D1, CIF, 480x240 (1-30fps)
Compression	H.265, H.264
Bitrate Control	VBR, CBR (64Kbps - 5Mbps)
Multiple Streaming	3 streams

### Audio Specifications

Audio Compression	G.711A / G.711U
-------------------	-----------------

### Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, 802.1x, UPnP, HTTP, HTTPS, QoS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/Mac address filtering, digest authentication
User Access	Max. 4 simultaneous users, Actual number of users may vary depending on bandwidth

### Interfaces

Ethernet	RJ45 Jack
Power	DC Jack
Audio In	3.5mm input, Built-in mic
Audio Out	No
Card Slot	MicroSD, up to 256GB (not included)
Alarm In/Out	No
Reset	Yes

### Client Specifications

Web Browser Support	Chrome, Edge, Safari, Firefox, Internet Explorer
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard® Client, Speco Blue (iPhone® and Android™)

## System Specifications

PoE	Standard (IEEE 802.3af)
Detection Events	Line crossing, object detection, region intrusion and video blurring detection
Alert Triggers	Motion, Detection Events, SD card error
Image Settings	Watermark, IP address filtering, video mask, password protection, Corridor mode

## Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	< 5W
Operating Temperature	-40°F - 140°F
Operating Humidity	Less than 95 % (non-condensing)
Unit Dimensions	4.2" (Dia.) x 3.75" (H)
Unit Weight	1.0 lb.
Certifications	FCC

## Optional Accessories



**POEINJ**  
25.5W  
PoE Injector




**PSW5**  
12VDC  
Power Supply



**CMT1**  
Corner Mount




**PMT1**  
Pole Mount




**JB3**  
Junction Box




**WMT1\***  
Wall Mount



**CLT3\***  
Ceiling Mount



**CLTX1**  
Ceiling Mount  
4" Extension




**CLTX2**  
Ceiling Mount  
8" Extension


\*Requires JB3

## Camera Interfaces


**3.5mm Audio In**




**DC 12V**




**RJ45 PoE**



**Built-in Mic**





**up to 256GB**