



## 2nm 180° White, black anodized

200-024G2-B

2nm 180° White, black anodized  
Vertical mounted with 0.75m cable

Specifications	
Number	200-024G2-B
Light Color	White
Dimensions metric	104 mm x 37 mm x 45 mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>5.4cd
Dimensions imperial	4.0" x 1.4" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,USCG
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438021037
IP rating	IP68
Power draw (W)	2,4
UPC Code	879343021160
Connection	0.7m cable

**Specifications**

<b>Current consumption (mA @ 12VDC)</b>	137
---	-----

<b>Lead time</b>	1-2 weeks
------------------	-----------

<b>Current consumption (mA @ 24VDC)</b>	80
---	----

<b>Vessel size</b>	Under 12M,12-20M,20-50M
--------------------	-------------------------

<b>Weight (Kg)</b>	0.27 Kg
--------------------	---------

<b>Weight (Oz)</b>	9.49 Oz
--------------------	---------